De Dietrich

Oven Ref.: DOP8574A



Product Highlights

Mode CHEF Exclusivity. In CHEF MODE, the oven will manage all cooking parameters.(temperature - cooking mode and time). The dish just needs to be placed at the rack height recommended on the display, and it will be cooked to perfection. That's it.

Low temperature cooking With its finetuned temperature management set below 100°C, this exclusive program is ideal for cooking meat poultry and fish in an homegeneous regular and soft manner. It gives cooking results of an incomparable tenderness

| GENERAL | |
|-------------------------------------|-------------|
| Brand | DE DIETRICH |
| Commercial code | DOP8574A |
| Availability of spare parts (years) | 20 |

| PRODUCT DETAILS | |
|---|------------------|
| Alternative colors available | |
| Energy efficiency class (1st cavity) | A+ |
| Colour | Black |
| Ean code | 3660767977815 |
| Conventional energy consumption (kWh) 1st cavity) | 0,70 |
| Fan forced energy consumption (kWh) | 1.10 |
| Construction type | Built-in |
| Cooking mode | Multi-function + |
| Type of cleaning | Pyrolytic |
| Nombre de cavités | 1 |
| Energy input | Electricity |
| Type of oven | Simple |

| CONTROL PANEL | |
|---------------------------------|----------------|
| Colour of the panel | Black |
| Start and end of cooking time | |
| Material of the control panel | Metal + glass |
| Name of the Display | |
| Number of knobs | 1 |
| Type of functions without timer | Cooking Method |

| DOOR | |
|-------------------------------|----------------------|
| Door colour | Black |
| Type of door | Cool door |
| Door Material | Metal + glass |
| Number of glass panel on door | 4 |
| Door opening | Drop down,Soft Close |

| CAVITY 1 | |
|-------------------------------------|-------------|
| Dimensions of the cavity HxWxD (mm) | 382X474X405 |
| Name of the cavity | |
| | |
| Temperature control | |
| Smoke filtration system | catalyseur |
| Cavity capacity (L) | 73 |

| LIGHTING | |
|--------------------|--------------------|
| Door opening light | Yes |
| Number of bulb | 1 |
| Light position | Front;Lateral;Left |
| Type of bulb | Halogen |

| ACCESSORIES | |
|------------------------------|--|
| Accessories | 00 |
| Number of grids | 4 |
| Number of trays | |
| Telescopic racks and shelves | |
| Turnspit | 00 |
| Type of grid | 2 Flat grids security;2 mid-grids spéciales arrosage |
| Type of dishes and trays | Dish tray 45 mm |

De Dietrich

Oven Ref.: DOP8574A

| CONSUMPTION VALUES | |
|--|------|
| Energy consumption in forced convection mode for gas oven (MJ) | |
| Energy consumption in conventional mode for gas oven (MJ) | |
| Energy consumption for 1hr at 175°/200°C (kWh) | 0.45 |
| Energy consumption for pre-heating (kWh) | 0.36 |
| 80 minutes Pyro cycle Consumption (kWh) | 3 |
| Indice d'Efficacité Energétique (EEI) (kWh) | 81,4 |
| Pre-heating time (min) | 7 |

| SAFETY | |
|--------------------------|---------|
| Safety devices | |
| Certificates of approval | CB/;EEC |

| COOKING FUNCTIONS OF T | HE OVEN |
|-------------------------------|------------------------------------|
| Cooking functions | Stop |
| Cooking functions | Chaleur tournante |
| Cooking functions | Combined Heat |
| Cooking functions | Conventional |
| Cooking functions | Eco |
| Cooking functions | Fanned Grill |
| Cooking functions | Bottom+fan |
| Cooking functions | Grill/4 niveaux |
| Cooking functions | Warm keeping |
| Cooking functions | Defrosting |
| Cooking functions | Bread |
| Cooking functions | Drying |
| Cooking functions | Shabbat |
| Cooking functions | Low Temperature Cooking 10 recipes |
| Cooking functions | CULINARY GUIDE |
| Cooking functions | Ics 9 recipes |
| Cooking functions | Pyrolysis |

| HEATING ELEMENTS | | |
|------------------------------|------|--|
| Circular heating element (W) | 2000 | |
| Vault cavity (W) | 00 | |
| Grill element (W) | 2100 | |
| Gas gril(W) | 00 | |
| Bottom element power (W) | 1200 | |
| Gas heating element (W) | 00 | |

| OTHER ENERGIES | |
|----------------------------|----|
| Alternative gas type | 00 |
| Type of gas by default | 00 |
| Gas connection rating (kW) | |
| Gas connection Norme EN30 | 00 |

| CONNECTIONS | |
|---------------------------------------|---------|
| Frequency (Hz) | 50/60 |
| Current (Amp) | 16 |
| Lenght of electrical supply cord (cm) | 115 |
| Electrical connection rating (KW) | 3.385 |
| Voltage (V) | 220-240 |
| Type of plug | Without |

| DIMENSIONS | |
|---|-------------|
| Built in dimensions HxWxD(mm) | 585X560X550 |
| Dimensions of the packed product HxWxD (mm) | 670X640X660 |
| Dimensions of the product HxWxD (mm) | 592X592X609 |
| Gross weight (kg) | 40.4 |
| Net weight (kg) | 39.1 |